



Prologue

Prologue

HATTERSLEY Bronze Fixed Orifice Double Regulating Valve

Figure No: 1732, 1732M - 1732L - 1732C - 1732MC - 1732LC

Bronze Fixed Orifice Double Regulating Valve

Pressure Rating: PN20

Material: Bronze

(FODRV) PN20 (Threaded): PN16 (Compression)

- **Pressure/Temperature Rating**

- BS 5154 PN20 Series B - restricted
- 17.2 bar at 120^oC
- 20 bar at -10 to 100^oC
- Compression Ends
- 5 bar at 120^oC
- 6 bar at 110^oC
- 10 bar at 65^oC
- 16 bar from 2 to 30^oC

- **Test Pressure**

- Body: 30 bar
- Seat: 22 bar

- **Specification**

- Kitemarked to BS7350
- Handwheel operated
- Numerical indicator

- Inside screw non-rising handwheel
- Characterised regulating disk
- Integral fix orifice
- Supplied with 2 Fig 631 test points
- Flow charts available
- End connections threaded
- Sizes 1" to 2" to ISO 7 parallel
- Sizes 1/2" and 3/4" to ISO 228 parallel
- Sizes DN15 and DN20 when used with compression adaptors suitable for copper pipe to BS EN 1057 R250 (half hard)
- WRAS approved product

[Vendor Information](#)