Prologue

Prologue

HATTERSLEY Bronze Fixed Orifice Double Regulating Valve

Figure No: 1732, 1732M - 1732L - 1732C - 1732MC - 1732LC
Bronze Fixed Orifice Double Regulating Valve
Pressure Rating: PN20
Material: Bronze
(FODRV) PN20 (Threaded): PN16 (Compression)

- **Pressure/Temperature Rating**
  - BS 5154 PN20 Series B - restricted
  - 17.2 bar at 120ÂºC
  - 20 bar at -10 to 100ÂºC
  - Compression Ends
  - 5 bar at 120ÂºC
  - 6 bar at 110ÂºC
  - 10 bar at 65ÂºC
  - 16 bar from 2 to 30ÂºC

- **Test Pressure**
  - Body: 30 bar
  - Seat: 22 bar

- **Specification**
  - Kitemarked to BS7350
  - Handwheel operated
  - Numerical indicator

- Inside screw non-rising handwheel
- Characterised regulating disk
- Integral fix orifice
- Supplied with 2 Fig 631 test points
- Flow charts available
- End connections threaded
- Sizes 1â€• to 2â€• to ISO 7 parallel
- Sizes 1/2â€• and 3/4â€• to ISO 228 parallel
- Sizes DN15 and DN20 when used with compression adaptors suitable for copper pipe to BS EN 1057 R250 (half hard)
- WRAS approved product

Vendor Information